

COMMERCIAL



# SUPER 104



AVAILABLE DECK SIZES

104" RD

# SUPER 104

## SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak steering when you drive ours and drive theirs.

## HyperDrive® Hydro System

Features industrial-grade pumps and motors to handle tough jobs and long days.

## I3M Suspension Seat

High-back seat with adjustable armrests and 3-inch travel range.

## Commercial-Grade Engines

Vanguard Big Block™, Vanguard Big Block™ EFI with Oil Guard, Kawasaki FX1000, and FX1000 EFI engine options.

## Hydraulic Deck Height Adjustment

Raising and lowering your cutting height has never been easier.

## Hydraulic Wings

Easily raise and lower wings for transporting.



## 80" Transport Width

Fits most trailers making it easy to transport from job-to-job.

## 104" Width of Cut

Widest and most productive commercial zero-turn available



# SUPER 104

- ✓ **104" Width of Cut**  
Widest and most productive commercial zero-turn available.
- ✓ **80" Transport Width**  
Fits most trailers making it easy to transport from job-to-job.
- ✓ **HyperDrive® Hydro System**
- ✓ **Mows a football field in under 10 minutes.**



## ACCESSORIES

- ▶ Mulch kit
- ▶ Steering lever extension kit
- ▶ Light kit
- ▶ Anti-scalp kit
- ▶ Flasher kit
- ▶ Beacon kit
- ▶ Flex Forks®
- ▶ Hitch kit
- ▶ Semi-pneumatic wheel/tire  
15 x 6 Black

**INDUSTRY'S  
BEST WARRANTY**

**5** YEAR | **3000**  
YEAR | HOUR

**PUMPS  
AND  
MOTORS**





# SUPER 104

## ENGINE

Manufacturer	Vanguard, Kawasaki
HP	35HP - Kawasaki FX1000 36HP - Vanguard BIG BLOCK™ 37HP - Vanguard BIG BLOCK™ EFI w/ Oil Guard 38.5HP - Kawasaki FX1000 EFI (Per SAE J1995)
Displacement	Vanguard 993 cc, 999cc Kawasaki
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	5 year Vanguard    3 year Kawasaki

## DRIVE SYSTEM

Type	Dual hydrostatic
Pumps	Danfoss DDC20
Wheel Motors	Parker TG0360
Hydraulic Lines	Stainless steel Parker seal loc technology
Reservoir Capacity	3 gallons
Speed	Up to 11 mph
Parking Brakes	Patented automatic

## DECKS

Cutting Width	Rear discharge: 104"
Cutting Heights	1" - 5.5"
Deck Lift	Hydraulic powered
Depth	5.5"
Blades	5
Blade Length	1 - 23.86" x 2.50" x .20" CW 1 - 23.86" x 2.50" x .20" CCW 1 - 20.50" x 2.50" x .20" CCW 2 - 20.50" x 2.50" x .20" CW
Blade Tip Speed	Wing Decks: 15800; Center Deck: 15500
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1 per deck
Drive	Electric PTO clutch
Construction	11 ga. welded steel
Spindle Mounts	Reinforced 7 ga. doubler
Impact/Trim Areas	1.5" x .375" steel bar

## CONSTRUCTION

Frame	1.5" x 3.0" steel tubing
Front Caster Wheels	Mounted & tapered wheel bearings & debris cap
Front Caster Forks	Fabricated 1/2" steel

## GENERAL

Seat	I3M suspension seat, adjustable armrests and back
Fuel Capacity	12 gallons
Cup Holder	Yes
Front Tire	15 x 6.0 - 6
Drive Tire	26 x 12 - 12
Wing Tire	11 x 4 semi-pneumatic

## DIMENSIONS

Weight	2500 lbs
Height w/rops up	71.5"
Height w/rops Folded	54"
Length	95.5"
Width	106.1" wings down 80.0" wings up at gauge wheels 72.5" wings up at deck base
Tire Width	60.3"
Trim Side	23.2"

## PRODUCTIVITY\*

Acres Per Hour	9.24
----------------	------

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

\*\* Specifications are subject to change without notice.

## LIMITED WARRANTY

**2** YEAR | **NO** HOUR LIMIT **OR** **5** YEAR | **500** HOUR

LIMITED  
**LIFETIME WARRANTY**  
ON THE FRAME



Visit [hustlerturf.com](http://hustlerturf.com)

and try our compare products tool!